

NESTLE LINE LASER NCL-2

MODEL NO. 16102001



MIT DEN BESTEN MESSEN

LINE LASER FOR INDOOR WORKING

- Set up and start work! The NESTLE NCL-2 has an integrated pendulum compensator which does the fine adjust by itself.
- An outstandingly visible laser line. You could use a receiver for longer distances - switch into the pulse mode.
- No operating errors - clearly arranged control panel.
- It is possible to fix the horizontal and vertical laser lines to operate in every position.
- Low-bat indicator starts blinking when battery voltage under <3 Volt.
- The NESTLE NCL-2 is a small sized instrument for nearly every indoor work.
- The laser has a 1/4" thread to mount a tripod. This makes the laser more flexible in its application.
- An acoustical alarm signal sounds out, if the laser cannot do the fine adjusting.
- Horizontal and vertical laser line - angle of reflected beam 120°.

APPLICATIONS

- The NESTLE NCL-2 is protected by a solid casing with rubber coating for more safety at construction.
- Solid construction of the NCL-2 is ideal for the rugged daily use.
- Simple handling to be fast and precision.

SPECIFICATIONS

Tolerance horizontal line	$\pm 3 \text{ mm to } 10\text{m}$
Tolerance vertical line	$\pm 2.5 \text{ mm to } 10\text{m}$
Self-levelling zone	$4^\circ \pm 0.5^\circ$
Operating area / with receiver	20m / 50 m with receiver
Operating time	<8 hours
Laser	635 nm visible, class 2
Storage temperature	-20°C to +60°C
Dimensions	119 x 62 x 95 mm
Weight	480 g
Protection class	IP 45

ACCESSOIRES

Delivery includes:

- NESTLE NCL-2, 3x AA batteries and bag.

Optional available by NESTLE:

- Magnet Support, Model no. 21133000.
- Receiver Decto, Model no. 16814000.

